

## Electrostatic Discharge Simulator

## EDS 30T



### In Compliance With

- > IEC 61000-4-2
- > IEC/ EN 61000-6-2
- > IEC/EN 61000-6-1
- > IEC/EN 61326
- > IEC 61340-3-1
- > GB/T 17626.2
- > ISO 14304
- > Bellcore GR-1089-Core
- > ITU-T K.20

### Introduction

The human body can sometimes generate voltages of up to several thousand volts from static electricity on objects or between two objects, which can cause electrical and electronic equipment circuits to malfunction or even damage. EDS 30T is a state-of-the-art intelligent electrostatic discharge generator with an output voltage of 30 kV. It is also China's first independently developed and produced electrostatic discharge simulator that integrates discharge gun head and touch screen control. It accurately simulates electrostatic discharge pulse interference in accordance with EN/IEC 61000-4-2 and other requirements, designed according to ergonomics. The LCD touch screen is simple and easy to operate, with AC and battery pack options for power supply, replaceable RC module, and built-in temperature and humidity meter, ensuring reliability in various testing scenarios.






### Features

- > Ergonomic design;
- > LCD touch screen;
- > All-in-one design (no base unit);
- > Changeable R/C networks;
- > Automatic polarity switching;
- > Battery or mains operation, long battery life;
- > Temperature and humidity monitoring;
- > Built-in standard test library;
- > Intelligent detection the failure of air discharge.






### Application Areas




- > Communication
- > IT
- > Telecom
- > Military
- > Medical
- > Avionics
- > Broadcast
- > New Energy
- > Railway

Technical Parameters	
Contact Discharge	200 V – 30,000 V (±5%)
Air Discharge	200 V – 30,000 V (±5%)
Voltage Step	100 V
Hold Time	> 5 s
Charge Resister	51MΩ
Polarity	Positive, negative
RC Module Recognition	Automatic recognition & LCD display
Temperature And Humidity	Built-in temperature and humidity meter with functions of record and protection
Repetition Frequency	Single /0.1/0.2/0.5/1/2/5/10/20 Hz
Trigger Mode	Manual/automatic
Pulse Counter	1-9999
Contact Discharge	150pF/330 ohm
Rise Time	0.8 ns +/- 25%
Quick Start Test Program	Simple and easy to reset data online
Evaluate Procedure	Contact discharge test at 20 Hz, evaluate the test points of DUT
Standard Test Procedure	accord with EN/IEC61000-4-2

Standard Accessories	
1. Discharge Gun 	Discharge gun and control 1 PCS
2. High Voltage Generator 	Programmable high voltage source 1 PCS
3. Standard RC Modules EDS 20H-RC 	150 pF / 330 ohm (default) , removable
4. Discharge Tip EDS 20H-CONT 	Contact discharge tip
5. Discharge Tip EDS 20H-AIR 	Air discharge tip
6. Grounding wire	2 m
7. Package	Carrying case
8. Documents	Factory inspection report and user manual

General Parameters	
Weight	Approx. 12.0 kg
Weight (EDS Gun)	Approx. 2.0 kg
Temperature	15℃-35℃ (operation condition)
Humidity	30%-60% (operation condition)
Air Pressure	86 kPa-106 kPa
Working Power Supply	100 V - 240 V (±10%) ; 50/60 Hz (default AC 220 V 50 Hz for China Mainland)

Optional Accessories		
1. RC Modules 	150 pF/2000 ohm (EDS) 330 pF/2000 ohm (EDS) 330 pF/330 ohm (EDS) 100 pF/1500 ohm (EDS) 150 pF/150 ohm (EDS) 500 pF/500 ohm (EDS)	500 pF/5000 ohm (EDS) 200 pF/0 ohm (EDS) 500 pF/0 ohm (EDS) 500 pF/100 ohm (EDS) Customization is available for RC module.
2. 30 mm Air Discharge Tip EDS 30T-AIR (30mm) 	For 15 kV to 30 kV test	
3. Battery Box EDS01 	8*2600 mAh Ni-MH rechargeable batteries to replace AC source For contact discharge +30 kV, 1 Hz, approx. 8 h Dimension: 140 mm*100 mm*35 mm, weight 0.5 kg	
4. Battery Charger 	Used for charging for battery box EDS 01	
5. Electrostatic Discharge Desk 	Grounded HV resistor 2 x 470 kohm	
	Vertical coupling plane 500x500x3 mm	
	Horizontal coupling plane 1600x800x2 mm	
	Reference ground plane 2700x1800x2 mm	
	Test table 1600x800x800 mm, solid wood, meet IEC 61000-4-2 requirements	

Optional Accessories	
6. ESD Calibration Kit EDS CALA 	Used for waveform calibration as per IEC/EN61000-4-2, including 2 ohm target /4 GHz, attenuator, coaxial cable, user manual
7. Attenuator JZ602 	Impedance: 50 ohm; Attenuation: 20 dB
8. Attenuator JZ603 	Impedance: 50 ohm; Attenuation: 20 dB
9. EDS 20H-PC Communication EDS 20H-REMOTE	Realize the remote control function of the upper computer software to the instrument
10. PC Software Corelab	<ul style="list-style-type: none"> <li>&gt; Compatible with Windows 7, Windows 8 and Windows 10 operating systems</li> <li>&gt; support Ethernet interface and serial interface communication mode</li> <li>&gt; support scheduling testing, test sequence parameters and the key test, the operation is simple</li> <li>&gt; can be set up customer information, automatic generation of test reports, and support the export of test report, the convenient user record data in real time</li> </ul>



## **SUZHOU 3CTEST ELECTRONIC CO., LTD.**

Add.: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

Tel: +86 (0)512 6807 7192      Fax: +86-512-68079795

Sales Email: [globalsales@3ctest.cn](mailto:globalsales@3ctest.cn)      Service Email: [service@3ctest.cn](mailto:service@3ctest.cn)

[www.3c-test.com](http://www.3c-test.com)