



Coupling and Decoupling Networks

CDN 405M40-32

Features

- IEC 61000-4-5
- EN 61000-4-5
- GB/T 17626.5

- > Used for 4 unshielded unbalanced lines;
- > All sockets are safe banana plugs, ensuring maximum safety for users;
- > Suitable for 1.2/50 μ s, 8/20 μ s combination waves.

Introduction

CDN 405M40-32 is suitable for coupling and decoupling testing networks of data and control lines for 4 unshielded asymmetric lines during surge testing, with a peak voltage of up to 6 kV. Design strictly in accordance with the requirements of GB/T 17626.5 and IEC 61000-4-5 standards. All sockets in the product are safe banana plugs, ensuring maximum safety for users.

Application Areas



Technical Parameters

Standard	IEC 61000-4-5
Coupled Waveform	1.2/50 μ s、8/20 μ s
Output Impedance	40 Ω ±5%
Pulse Voltage	6 kV
Coupling Components	0.5 μ F capacitor
Coupling Mode	4 unshielded asymmetric wires
Communication Interface Specifications	Banana head 4 mm
Working Voltage	Max 250 V AC/DC
Working Current	Max 32 A AC/DC
Decoupling Inductance	1.5 mH
Fan Voltage and Current	24 VDC/2 A

General Parameters

Weight	Approximately 24 kg
Size	475 mm x 235 mm x 195 mm (length x width x height)
Shell Material	Aluminum material
Ambient Temperature	15 ° C -35 ° C
Relative Humidity	45% -75%

Standard Accessories

Test line, Impedance Module NR40 Ω , Coupling Module CD-C05, Decoupling Module DP-C250, Adapter.

SUZHOU3CTEST ELECTRONIC CO., LTD

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China
 Sales Email: globalsales@3ctest.cn Service Email: service@3ctest.cn
 Tel: + 86 - 512 - 68077192 Web: www.3c-test.com

